

## TE12 - TE14 SERIES COMPARISON



### ProLite

**TE5512MIS-B3AG | TE6512MIS-B3AG | TE7512MIS-B3AG  
TE8612MIS-B3AG | TE9812MIS-B3AG**

**TE6514MIS-B2AG | TE7514MIS-B2AG | TE8614MIS-B2AG**

Display characteristics	
Size category	55" (138.8cm), 65" (163.9cm), 75" (189.3cm), 86" (217.4cm), 98" (247.7cm)
Panel type	IPS 86" VA
Anti-Glare Coating	✓
Zero Air-Gap	✓
Touch technology	PureTouch-IR
Touch points	40 (5pt writing)
Native resolution	3840 x 2160 (4K UHD)
Panel brightness (cd/m <sup>2</sup> )	400
Light transmittance	88% 86" 92%
Static contrast	1200:1 86" 4000:1
Max. Operating time	24/7
Interfaces & connectors	
Video IN / OUT	VGA, HDMI x3 (2.0), HDMI (OUT) x1 (2.0), USB-C x1 (3.2, 65W PD, Touch)
Audio IN / OUT	MiniJack (IN & OUT), S/PDIF
Speakers	Speakers 2x 16W
Microphone	✗
Control	RS232c x1 (DSUB 9pin), RJ45 (LAN) x2 (IN/OUT, Auto switch for PC & Android, 1000MB), USB Touch x2
USB	5x (front: 2x 3.2, 1x USB-C 3.2 (65W PD), right: 2x 3.2)
Features	
Android / iiWare	Android 11 OS / iiWare 10
iiyama Share & Eshare	✓
Ambient light sensor	✓
OTA firmware update	✓
Hardware	CPU: 4*A55, GPU: Mali G52, RAM: 8GB, ROM: 64GB
Included / optional	
Wifi6 Collaboration module	OWM002
Metal housing	✓
Mounting brackets for NUC / webcam	✓
Touch pens (dual function tips)	4x, Anti-Bacterial
Optional OPS Slot PC	OPC51204BC-1

Display characteristics	
Size category	65" (163.9cm), 75" (189.3cm), 86" (217.4cm)
Panel type	VA
Anti-Glare Coating	✓
Zero Air-Gap	✓
Touch technology	PureTouch-IR*, Palm Rejection
Touch points	50 (10pt writing)
Native resolution	3840 x 2160 (4K UHD)
Panel brightness (cd/m <sup>2</sup> )	435
Light transmittance	92%
Static contrast	4000:1 75" 5000:1
Max. Operating time	24/7
Interfaces & connectors	
Video IN / OUT	HDMI x4 (2.0), HDMI (OUT) x1 (2.0, MSD (Multi-Screen Display)), DisplayPort x1 (2.1), USB-C x2 (3.2, 1x front: 100W PD, 1x back: 15W PD, Touch, DP 1.2 Alt Mode), USB-C (OUT) x1 (3.2, 5W PD, Touch, MSD (Multi-Screen Display)), DP 1.2 Alt Mode)
Audio IN / OUT	MiniJack (IN & OUT), S/PDIF
Speakers	Speakers 2x 18W (facing up), 2x 8W (front facing)
Microphone	Built-in 8-Array Microphone (8m voice pick-up)
Control	RS232c x1 (DSUB 9pin), RJ45 (LAN) x2 (IN/OUT, Auto switch for PC & Android, 1000MB), USB Touch x2
USB	6x ( front: 2x 3.2, 1x USB-C 3.2 (PD 100W), right: 2x 3.2, 1x USB-C 3.2 (PD 15W))
Features	
Android / iiWare	Android 13 OS / iiWare 12E (Including Google EDLA)
iiyama Share & Eshare	✓
Ambient light sensor	✓
OTA firmware update	✓
Hardware	CPU: 4*A76 + 4*A55, GPU: Mali G610, RAM: 8GB, ROM: 64GB
Included / optional	
Wifi6 Collaboration module	OWM002
Metal housing	✓
Mounting brackets for NUC / webcam	✓
Touch pens (dual function tips)	4x, Anti-Bacterial
Optional OPS Slot PC	OPC51204BC-1

All trademarks and registered trademarks acknowledged. Changes and mistakes in graphics and specs reserved. Specifications subject to change without notice. Copyright by iiyama International. Stand 10/2024.