



Full HD monitor od 21.5" sa VA panelom

ProLite XU2294HSU sa VA panelom obezbeđuje preciznu i doslednu reprodukciju boja sa širokim uglovima gledanja. Sa elegantnim tankim okvirom, monitor je idealan izbor za povezivanje sa više monitora, kompatibilan sa bilo kojim iiyama dodatkom za duple ili trostruke monitore za konfiguracije radnog prostora po meri. Opremljen zvučnicima, USB 3.0 čvorištem sa 2 porta, utičnicom za slušalice, HDMI i DisplayPort priključcima i funkcijom redukcije plavog svetla za smanjenje zamora očiju. Sve to čini ovaj 22" ekran idealnim za bilo koju kancelariju ili kućnu kancelariju.



VA matrica

Tehnologija VA panela nudi veći kontrast, tamnije crne i mnogo bolje uglove gledanja od standardne TN tehnologije. Ekran će izgledati dobro bez obzira pod kojim uglom gledate.



Bez treperenja + Plavo svetlo

Vrhunsko rešenje za udobnost i zdravlje Vaših očiju. Monitori bez treperenja sa funkcijom reduktora plave svetlosti značajno smanjuju naprezanje i umor uzrokovan treperenjem i emitovanjem plave svetlosti običnih monitora.

01 KARAKTERISTIKE EKRANA

Dizajn	3-side borderless
Dijagonala	21.5", 54.5cm
Panel	VA, mat završna obrada
Osnovna rezolucija	1920 x 1080 @75Hz (2.1 megapixel Full HD)
Osnovna rezolucija	75Hz
Format ekrana	16:9
Osvetljenje	250 cd/m ²
Statički kontrast	3000:1
Napredni kontrast	80M:1
Vreme odziva (MPRT)	1ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	16.7mln (sRGB: 99%; NTSC: 72%)
Horizontalna sinhronizacija	30 - 85KHz
Vidljiva površina Š x V	478.7 x 260.3mm, 18.78 x 10.2"
Razmak piksela	0.249mm
Boja	mat, crna

02 KONEKTORI / KONTROLE

Ulaz signala	HDMI x1 DisplayPort x1
USB HUB	x2 (v. 3.2 (Gen 1, 5Gbit; DC5V, 900mA))
HDCP	da
Priključak za slušalice	da

03 KARAKTERISTIKE

Smanjeno emitovanje plave svetlosti	da
Bez treperenja	da
Adaptive Sync podrška	da
Dodatno	i-Style Boje
OSD jezici	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Zvučnici	2 x 2W
Pogodnost	Kensington-lock™ priprema, DDC2B, Mac OSX

04 MEHANIČKI

Podešavanje položaja prikaza	nagib
Ugao nagiba	22° gore; 54° dole
VESA montiranje	100 x 100mm
Sistem upravljanja kablovima	da

05 UKLJUČENI DODACI

Kablovi	Strujni kabl, USB, HDMI
Ostalo	kratko uputstvo, bezbednosni vodič

06 UPRAVLJANJE NAPAJANJEM


Napajanje	interna
Potrošnja energije	% 1W tipično, 0.5W stand by, 0.3W isključen

07 ODRŽIVOST

Propisi	CE, TÜV-Bauart, VCCI-B, PSE, RoHS podrška, ErP, WEEE, REACH, UKCA
Klasa energetske efikasnosti (Regulation (EU) 2017/1369)	D
EPEAT	*registration varies by country, go to www.epeat.net for details
REACH SVHC	iznad 0.1%: Olova

08 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	493.5 x 363 x 200mm
Dimenzije kutije Š x V x D	564 x 120 x 386mm
Težina (bez kutije)	2.7kg
Težina (sa kutijom)	3.4kg
EAN kod	4948570120772



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.